Recessed ceiling downlights with symmetrical light distribution - wide beam

Housing: Constructed of die-cast and extruded aluminum. Housing is provided with mounting clamps that provide a vibration proof installation. Rough-in housing constructed of glavanized steel with through wiring box. Rough-in housing included. Die castings are marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy.

Enclosure: Tempered clear glass, retained by a one piece, diecast aluminum frame threaded into luminaire housing. Internal reflector made from pure, anodized aluminum. Fully gasketed for weather tight operation using a molded silicone gasket.

Electrical: 12.7W LED luminaire, 15.5 total system watts, -30°C start temperature. EldoLED 0-10V dimmable driver mounted to the junction box of the ceiling pan for easy maintenance. The LED driver provides smooth and flicker free dimming down to 0.1% and is compatible with both sink and current source controllers. Optional Dali dimmable driver available, consult factory for details. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with an 85 CRI. Available in 4000K (85 CRI); add suffix K4 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

 \mbox{CSA} certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

Weight: 1.4 lbs.

Luminaire Lumens: 1066



+	Recessed ceiling downlights · wide beam				
	Lamp	β	Α	В	С
55 926	12.7W LED	86°	55/	31/.	18

β = Beam angle

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:

